

AMENDMENT TO THE CLAIMS

1. (Original) A computer readable medium including instructions readable by a computer which, when implemented, cause the computer to resolve an overlapping ambiguity string in an input sentence of an unsegmented language by performing steps comprising:
  - segmenting the sentence into two possible segmentations;
  - recognizing the overlapping ambiguity string in the input sentence as a function of the two segmentations; and
  - selecting one of the two segmentations as a function of probability information for the two segmentations.
2. (Original) The computer readable medium of claim 1 and further comprising obtaining the probability information from a lexical knowledge base.
3. (Original) The computer readable medium of claim 2 wherein the lexical knowledge base comprises a trigram model.
4. (Original) The computer readable medium of claim 2 wherein selecting one of the two segmentations comprises classifying the probability information.
5. (Currently Amended) The computer readable medium of claim 4 wherein classifying comprises classifying using Naïve Bayesian Classification.
6. (Original) The computer readable medium of claim 1 wherein segmenting the sentence comprises performing a Forward Maximum

Matching (FMM) segmentation of the input sentence and a Backward Maximum Matching (BMM) segmentation of the input sentence.

7. (Original) The computer readable medium of claim 6 wherein recognizing the overlapping ambiguity string comprises recognizing a segmentation  $O_f$  of the overlapping ambiguity string from the FMM segmentation and a segmentation  $O_b$  of the overlapping ambiguity string from the BMM segmentation.
8. (Original) The computer readable medium of claim 7 wherein selecting one of the two segmentations is a function of a set of context features associated with the overlapping ambiguity string.
9. (Original) The computer readable medium of claim 8 wherein the set of context features comprises words around the overlapping ambiguity string.
10. (Original) The computer readable medium of claim 8 wherein selecting one of the two segmentations comprises classifying the probability information of the set of context features and  $O_f$ .
11. (Original) The computer readable medium of claim 10 wherein selecting one of the two segmentations comprises classifying the probability information of the set of context features and  $O_b$ .
12. (Original) The computer readable medium of claim 8 wherein selecting comprising determining which of  $O_f$  or  $O_b$  has a higher probability as a function of the set of context features.

13. (Original) The computer readable medium of claim 1 wherein the unsegmented language is Chinese.

14. (Original) A method of segmentation of a sentence of an unsegmented language, the sentence having an overlapping ambiguity string (OAS), the method comprising the steps of:

- generating a Forward Maximum Matching (FMM) segmentation of the sentence;
- generating a Backward Maximum Matching (BMM) segmentation of the sentence;
- recognizing an OAS as a function of the FMM and the BMM segmentations; and
- selecting one of the FMM segmentation and the BMM segmentation as a function of probability information.

15. (Currently Amended) The method of claim 14 wherein the step of selecting includes determining a probability associated with each of the FMM segmentation of the overlapping ambiguity string and the BMM segmentation of the overlapping ambiguity string, ~~the C-scores comprising probability information.~~

16. (Currently Amended) The method of claim 15 wherein determining the probabilities information comprises using an N-gram model.

17. (Currently Amended) The method of claim 16 wherein determining the probabilities comprises using probability information about a first word of the overlapping ambiguity string.

18. (Currently Amended) The method of claim 17 wherein determining the probabilities comprises using probability information about a last word of the overlapping ambiguity string.

19. (Original) The method of claim 16 wherein using the N-gram model comprises using information about context words around the overlapping ambiguity string.

20. (Currently Amended) The method of claim 16 wherein using the N-gram model comprises using information about a string of words comprising a first word of the overlapping ambiguity string and two context words to the left of the first word. |

21. (Currently Amended) The method of claim 20 wherein using the N-gram model comprises using information about a string of words comprising a last word of the overlapping ambiguity string and two context words to the right of the last word. |

22. (Original) The method of claim 15 wherein selecting includes using Naïve Bayesian Classifiers.

23. (Original) The method of claim 14 and further comprising receiving information from a lexical knowledge base comprising a trigram model.

24. (Original) The method of claim 23 and further comprising receiving an ensemble of Naïve Bayesian Classifiers.

25. (Original) A method of constructing information to resolve overlapping ambiguity strings in an unsegmented language comprising the steps of:

- recognizing overlapping ambiguity strings
- in a training data;
- replacing the overlapping ambiguity strings
- with tokens;

generating an N-gram language model comprising  
information on constituent words of the  
overlapping ambiguity strings.

26. (Original) The method of claim 25 wherein generating the N-gram language model comprises generating a trigram model.

27. (Original) The method of claim 25 and further comprising  
generating an ensemble of classifiers as a function of the N-gram  
model.

28. (Original) The method of claim 25 wherein recognizing the  
overlapping ambiguity strings comprises:

generating a Forward Maximum Matching (FMM)  
segmentation of each sentence in the training  
data;  
generating a Backward Maximum Matching  
(BMM) segmentation of each sentence in the training  
data;  
recognizing an OAS as a function of the FMM and the  
BMM segmentations of each sentence in the  
training data.

29. (Original) The method of claim 28 and further comprising  
generating an ensemble of classifiers as a function of the N-gram  
model.

30. (Currently Amended) The method of claim 29 wherein generating  
the ensemble of classifiers includes approximating ~~an~~  
probabilities of the FMM and BMM ~~a~~-segmentations of each  
overlapping ambiguity string as being equal to the product of  
individual unigram probabilities of individual words in the FMM and

BMM segmentations respectively, of the overlapping ambiguity string. |

31. (Currently Amended) The method of claim 30 wherein generating the ensemble of classifiers includes approximating a joint probability of a set of context features conditioned on an existence of one of the segmentations of each overlapping ambiguity string as a function of a corresponding probability of a leftmost and a rightmost word of the corresponding overlapping ambiguity string. |